

Package ‘STDistance’

June 21, 2026

Title Spatial Transcriptomics Distance Calculation and Visualization

Version 0.6.8

Description Analysis of spatial relationships between cell types in spatial transcriptomics data. Spatial proximity is a critical factor in cell-cell communication. The package calculates nearest neighbor distances between specified cell types and provides visualization tools to explore spatial patterns. Applications include studying cell-cell interactions, immune microenvironment characterization, and spatial organization of tissues.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.2

Depends R (>= 4.0.0)

Imports dplyr, ggplot2, Hmisc, scales, stats, RColorBrewer, tidyr,

Suggests testthat, knitr, rmarkdown

LazyData true

VignetteBuilder knitr

NeedsCompilation no

Author Zixiang Wang [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5252-9764>>),
Lei Yang [aut],
Zhaojian Liu [aut]

Maintainer Zixiang Wang <wangzixiang@sdu.edu.cn>

Repository CRAN

Date/Publication 2026-06-21 14:30:14 UTC

Contents

calculate_correlations	2
calculate_nearest_distances	3
distance_results	4
metadata	5
normalize_spatial	6

plot_distance_boxplot	7
plot_radial_distance	8
posi	9
tissue_posi	10
tissue_posi_normalized	11
visualize_spatial_gradient	12
visualize_spatial_multinetwork	14
visualize_spatial_network	15

Index 17

calculate_correlations

Perform correlation analysis between spatial features and distance metrics with visualization

Description

Perform correlation analysis between spatial features and distance metrics with visualization

Usage

```
calculate_correlations(
  spatial_data,
  distance_results,
  spatial_feature,
  distance_metric,
  id_col = "Newbarcode",
  method = "pearson",
  plot = TRUE,
  plot_title = NULL
)
```

Arguments

spatial_data	Spatial data containing feature columns and Newbarcode identifier
distance_results	Distance results containing distance metrics and Newbarcode identifier
spatial_feature	Column name from spatial_data to use for correlation (e.g., "gen2_SPLIz_numeric")
distance_metric	Column name from distance_results to use for correlation (e.g., "Epithelial_cells_A")
id_col	Column name used to join spatial_data and distance_results (default: "Newbarcode")
method	Correlation method ("pearson", "spearman", "kendall")
plot	Logical, whether to generate a scatter plot
plot_title	Title for the scatter plot (optional)

Value

A list containing correlation results and ggplot object (if plot=TRUE)

Examples

```
calculate_correlations(spatial_data = posi,
  distance_results = distance_results,
  spatial_feature = "gen2_SPLIz_numeric",
  distance_metric = "Epithelial_cells_A",
  id_col = "Newbarcode",
  method = "pearson",
  plot = TRUE,
  plot_title = "Correlation between Gene Expression and Distance")
```

calculate_nearest_distances

Calculate nearest distances between cell types

Description

Calculate nearest distances between cell types

Usage

```
calculate_nearest_distances(
  spatial_data,
  reference_type,
  target_types,
  x_col = "pxl_row_in_fullres",
  y_col = "pxl_col_in_fullres",
  id_col = "barcode",
  type_col = "Epi_strom",
  sample_col = NULL
)
```

Arguments

spatial_data	A data frame containing spatial coordinates and cell type info
reference_type	The reference cell type to calculate distances from
target_types	Vector of target cell types to calculate distances to
x_col	Column name for x-coordinates
y_col	Column name for y-coordinates
id_col	Column name for cell identifiers
type_col	Column name for cell type information
sample_col	Column name for sample identifiers; when provided, distances are calculated within each sample independently so cells from different tissue sections are never compared

Value

A data frame with nearest distances for each reference cell

Examples

```
calculate_nearest_distances(posi, reference_type="Macrophage",
                           target_types=c("Epithelial_cells_A", "Epithelial_cells_B",
                                           "Epithelial_cells_C", "Epithelial_cells_D"),
                           id_col = "Newbarcode",
                           type_col = "celltype_ABCDepi",
                           sample_col = "orig.ident")
```

distance_results	<i>distance_results</i>
------------------	-------------------------

Description

A data frame with nearest distances for each reference cell

Usage

```
data("distance_results")
```

Format

A data frame with 18 observations on the following 5 variables.

Newbarcode a character vector

Epithelial_cells_A a numeric vector

Epithelial_cells_B a numeric vector

Epithelial_cells_C a numeric vector

Epithelial_cells_D a numeric vector

Details

A data frame with nearest distances for each reference cell.

Source

This study.

References

Wang, Z., Yang, L., Yang, S., Li, G., Xu, M., Kong, B., Shao, C., & Liu, Z. (2025). Isoform switch of CD47 provokes macrophage-mediated pyroptosis in ovarian cancer. *bioRxiv*, 2025.2004.2017.649282. <https://doi.org/10.1101/2025.04.17.649282>

Examples

```
data(distance_results)
## maybe str(distance_results) ; plot(distance_results) ...
```

metadata	<i>Metadata</i>
----------	-----------------

Description

Metadata of a Seurat Object.

Usage

```
data("metadata")
```

Format

A data frame with 293 observations on the following 9 variables.

`orig.ident` a character vector
`nCount_Spatial` a numeric vector
`nFeature_Spatial` a numeric vector
`nCount_SCT` a numeric vector
`nFeature_SCT` a numeric vector
`integrated_snn_res.0.8` a numeric vector
`seurat_clusters` a numeric vector
`celltype_ABCDepi` a character vector
`gen2_SPLiZ_numeric` a numeric vector

Details

Metadata dataframe can be exported from Seurat Object as follows. The Seurat Object should be fully annotated and the metadata dataframe should included: `orig.ident`, `celltype`, the target gene expression, splicing index (`SpliZ`), etc.

Source

This study.

References

Wang, Z., Yang, L., Yang, S., Li, G., Xu, M., Kong, B., Shao, C., & Liu, Z. (2025). Isoform switch of CD47 provokes macrophage-mediated pyroptosis in ovarian cancer. *bioRxiv*, 2025.2004.2017.649282. <https://doi.org/10.1101/2025.04.17.649282>

Examples

```
data(metadata)
## maybe str(metadata) ; plot(metadata) ...
```

normalize_spatial	<i>Normalize spatial coordinates</i>
-------------------	--------------------------------------

Description

Normalize spatial coordinates

Usage

```
normalize_spatial(  
  data,  
  sample_col = "Sample",  
  x_col = "pxl_row_in_fullres",  
  y_col = "pxl_col_in_fullres",  
  min_value = 1,  
  max_value = 10000  
)
```

Arguments

data	A data frame containing spatial coordinates
sample_col	Column name specifying sample IDs
x_col	Column name for x-coordinates
y_col	Column name for y-coordinates
min_value	Minimum value for normalization range
max_value	Maximum value for normalization range

Value

A data frame with normalized coordinates

Examples

```
tissue_posi_normalized<-normalize_spatial(tissue_posi)
```

plot_distance_boxplot *Visualize Nearest Neighbor Distances with Boxplot and Mean \pm SEM*

Description

Creates a boxplot visualization of distance metrics with overlaid mean points and SEM error bars. Suitable for comparing multiple groups with potentially skewed distributions.

Usage

```
plot_distance_boxplot(  
  distance_result,  
  id_col = "barcode",  
  show_points = FALSE,  
  y_scale = c("original", "log10"),  
  palette = "Set2"  
)
```

Arguments

distance_result	A data.frame generated by calculate_nearest_distances(), containing distance measurements with columns: id_col + target_types.
id_col	Name of the column containing cell IDs (default: "barcode").
show_points	Logical, whether to overlay individual data points (default: FALSE).
y_scale	Method for y-axis scaling: "original" or "log10" (default: "original").
palette	Color palette name from RColorBrewer (default: "Set2").

Value

A ggplot2 object. Additional customization can be done using ggplot2 functions.

Examples

```
plot_distance_boxplot(distance_results, id_col = "Newbarcode")
```

plot_radial_distance *Radial Distance Visualization with Collision Avoidance*

Description

Creates a radial plot with automatic label placement to prevent overlaps between nodes and text labels.

Usage

```
plot_radial_distance(  
  distance_result,  
  reference_type,  
  id_col = "barcode",  
  scale_radius = 1,  
  show_labels = TRUE,  
  palette = "Set2",  
  label_padding = 0.15,  
  center_label_expansion = 1.5  
)
```

Arguments

distance_result	Data.frame from calculate_nearest_distances()
reference_type	Name of the reference cell type (center node)
id_col	Name of ID column (default: "barcode")
scale_radius	Scaling factor for layout (default: 1)
show_labels	Whether to show distance labels (default: TRUE)
palette	Color palette name (default: "Set2")
label_padding	Radial padding for labels (default: 0.15)
center_label_expansion	Center expansion for labels (default: 1.5)

Value

A ggplot2 object

Examples

```
plot_radial_distance(distance_results, id_col = "Newbarcode",  
  reference_type = "Macrophages", label_padding = 0.3,  
  show_labels = TRUE, palette = "Dark2")
```

posi

posi

Description

Merged spatial location and metadata information.

Usage

```
data("posi")
```

Format

A data frame with 293 observations on the following 18 variables.

Newbarcode a character vector
barcode a character vector
in_tissue a numeric vector
array_row a numeric vector
array_col a numeric vector
pxl_row_in_fullres a numeric vector
pxl_col_in_fullres a numeric vector
Sample a character vector
Sampleid a numeric vector
orig.ident a character vector
nCount_Spatial a numeric vector
nFeature_Spatial a numeric vector
nCount_SCT a numeric vector
nFeature_SCT a numeric vector
integrated_snn_res.0.8 a numeric vector
seurat_clusters a numeric vector
celltype_ABCDipi a character vector
gen2_SPLIz_numeric a numeric vector

Details

Merged spatial location and metadata information.

Source

This study.

References

Wang, Z., Yang, L., Yang, S., Li, G., Xu, M., Kong, B., Shao, C., & Liu, Z. (2025). Isoform switch of CD47 provokes macrophage-mediated pyroptosis in ovarian cancer. *bioRxiv*, 2025.2004.2017.649282. <https://doi.org/10.1101/2025.04.17.649282>

Examples

```
data(posi)
## maybe str(posi) ; plot(posi) ...
```

tissue_posi	<i>tissue_posi</i>
-------------	--------------------

Description

Position of the spots from spatial transcriptome data.

Usage

```
data("tissue_posi")
```

Format

A data frame with 9984 observations on the following 9 variables.

barcode a character vector
in_tissue a numeric vector
array_row a numeric vector
array_col a numeric vector
pxl_row_in_fullres a numeric vector
pxl_col_in_fullres a numeric vector
Sample a character vector
Sampleid a numeric vector
Newbarcode a character vector

Details

Please find the tissue_positions.csv from the spaceranger output files: `./out/spatial/tissue_positions.csv`
Multiple samples should be merged together, adding "samples" and "Newbarcode" columns.

Source

This study.

References

Wang, Z., Yang, L., Yang, S., Li, G., Xu, M., Kong, B., Shao, C., & Liu, Z. (2025). Isoform switch of CD47 provokes macrophage-mediated pyroptosis in ovarian cancer. *bioRxiv*, 2025.2004.2017.649282. <https://doi.org/10.1101/2025.04.17.649282>

Examples

```
data(tissue_posi)
## maybe str(tissue_posi) ; plot(tissue_posi) ...
```

```
tissue_posi_normalized
      tissue_posi_normalized
```

Description

Normalized tissue spots position.

Usage

```
data("tissue_posi_normalized")
```

Format

A data frame with 9984 observations on the following 9 variables.

barcode a character vector
in_tissue a numeric vector
array_row a numeric vector
array_col a numeric vector
pxl_row_in_fullres a numeric vector
pxl_col_in_fullres a numeric vector
Sample a character vector
Sampleid a numeric vector
Newbarcode a character vector

Details

Normalized tissue spots position.

Source

This study.

References

Wang, Z., Yang, L., Yang, S., Li, G., Xu, M., Kong, B., Shao, C., & Liu, Z. (2025). Isoform switch of CD47 provokes macrophage-mediated pyroptosis in ovarian cancer. *bioRxiv*, 2025.2004.2017.649282. <https://doi.org/10.1101/2025.04.17.649282>

Examples

```
data(tissue_posi_normalized)
## maybe str(tissue_posi_normalized) ; plot(tissue_posi_normalized) ...
```

```
visualize_spatial_gradient
```

Visualize spatial network with expression gradient

Description

Visualize spatial network with expression gradient

Usage

```
visualize_spatial_gradient(  
  spatial_data,  
  sample,  
  gradient_type,  
  fixed_type,  
  expression_col = "gen2_SPLIz_numeric",  
  x_col = "pxl_row_in_fullres",  
  y_col = "pxl_col_in_fullres",  
  type_col = "Epi_strom",  
  sample_col = "Sample",  
  fixed_color = "#A9C6D9",  
  line_color = "#666666",  
  gradient_palette = "C",  
  point_size = 1,  
  point_alpha = 0.8,  
  line_width = 0.3,  
  line_alpha = 0.6,  
  show_legend = TRUE,  
  legend_title = "Expression",  
  grid_major_color = "gray90",  
  grid_minor_color = "gray95",  
  border_color = "black",  
  background_color = "white"  
)
```

```
visualize_spatial_multinetwork
```

Visualize spatial relationships between multiple cell types

Description

Visualize spatial relationships between multiple cell types

Usage

```
visualize_spatial_multinetwork(
  spatial_data,
  sample,
  reference_type,
  target_types,
  x_col = "pxl_row_in_fullres",
  y_col = "pxl_col_in_fullres",
  type_col = "Epi_strom",
  sample_col = "Sample",
  color_palette = NULL,
  point_alpha = 0.7,
  line_alpha = 0.5,
  point_size = 1.5,
  line_width = 0.3,
  show_legend = TRUE
)
```

Arguments

<code>spatial_data</code>	Spatial coordinates data frame
<code>sample</code>	Sample name in the spatial transcriptome data
<code>reference_type</code>	Reference cell type (character vector of length 1)
<code>target_types</code>	Target cell type(s) (character vector of 1 or more)
<code>x_col</code>	Column name for x-coordinates
<code>y_col</code>	Column name for y-coordinates
<code>type_col</code>	Column name for cell type information
<code>sample_col</code>	Column name for sample identifiers (default: "Sample")
<code>color_palette</code>	Named vector of colors for cell types
<code>point_alpha</code>	Transparency level for points
<code>line_alpha</code>	Transparency level for connection lines
<code>point_size</code>	Size of points in plot
<code>line_width</code>	Width of connection lines
<code>show_legend</code>	Logical, whether to show legend

Value

A ggplot object showing the spatial relationships

Examples

```
visualize_spatial_multinetwork(posi, sample="SP8", reference_type="Macrophage",
                               target_type=c("Epithelial_cells_A", "Epithelial_cells_B"),
                               type_col = "celltype_ABCDipi")
```

```
visualize_spatial_network
```

Visualize spatial relationships between cell types

Description

Visualize spatial relationships between cell types

Usage

```
visualize_spatial_network(
  spatial_data,
  sample,
  reference_type,
  target_type,
  x_col = "pxl_row_in_fullres",
  y_col = "pxl_col_in_fullres",
  type_col = "Epi_strom",
  sample_col = "Sample",
  color_palette = c(Macrophage = "#90ee90", Epithelial_cells_A = "#377EB8"),
  alpha = 0.7
)
```

Arguments

<code>spatial_data</code>	Spatial coordinates data frame
<code>sample</code>	Sample name in the spatial transcriptome data
<code>reference_type</code>	Reference cell type
<code>target_type</code>	Target cell type
<code>x_col</code>	Column name for x-coordinates
<code>y_col</code>	Column name for y-coordinates
<code>type_col</code>	Column name for cell type information
<code>sample_col</code>	Column name for sample identifiers (default: "Sample")
<code>color_palette</code>	Named vector of colors for cell types
<code>alpha</code>	Transparency level for points and lines

Index

* datasets

- distance_results, 4
- metadata, 5
- posi, 9
- tissue_posi, 10
- tissue_posi_normalized, 11

calculate_correlations, 2

calculate_nearest_distances, 3

distance_results, 4

metadata, 5

normalize_spatial, 6

plot_distance_boxplot, 7

plot_radial_distance, 8

posi, 9

tissue_posi, 10

tissue_posi_normalized, 11

visualize_spatial_gradient, 12

visualize_spatial_multinetwork, 14

visualize_spatial_network, 15