

Package ‘pikchr’

June 14, 2026

Type Package

Title R Wrapper for 'pikchr' (PIC) Diagram Language

Version 1.1.1

Date 2026-06-14

Description An 'R' interface to 'pikchr' (<<https://pikchr.org>>, pronounced ``picture"), a 'PIC'-like markup language for creating diagrams within technical documentation. Originally developed by Brian Kernighan, 'PIC' has been adapted into 'pikchr' by D. Richard Hipp, the creator of 'SQLite'. 'pikchr' is designed to be embedded in fenced code blocks of Markdown or other documentation markup languages, making it ideal for generating diagrams in text-based formats. This package allows R users to seamlessly integrate the descriptive syntax of 'pikchr' for diagram creation directly within the 'R' environment.

License GPL (>= 2)

Encoding UTF-8

RoxygenNote 7.3.3

VignetteBuilder knitr

Imports cli, knitr, brio, htmltools, stringr, rsvg

Suggests kableExtra, rmarkdown

URL <https://strategicprojects.github.io/pikchr/>,
<https://github.com/StrategicProjects/pikchr>

BugReports <https://github.com/StrategicProjects/pikchr/issues>

Note This package makes use of the 'pikchr' source code created by Richard Hipp (<<https://pikchr.org>>).

Depends R (>= 4.0)

LazyData true

Config/Needs/website tidyverse/tidytemplate, rmarkdown

NeedsCompilation yes

Author Andre Leite [aut, cre],
Hugo Vaconcelos [aut],
Diogo Bezerra [aut],

Marcos Wasilew [aut],
Carlos Amorin [aut],
Richard Hipp [ctb],
Brian Kernighan [ctb]

Maintainer Andre Leite <leite@castlab.org>

Repository CRAN

Date/Publication 2026-06-14 19:20:02 UTC

Contents

google_fonts	2
pikchr	3
Index	5

google_fonts	<i>Google Font List</i>
--------------	-------------------------

Description

List of fonts and their styles on the Google Fonts site.

Usage

google_fonts

Format

'google_fonts' A data frame with 1,718 rows and 2 columns:

family Font family names

styles Font styles

Source

<<https://fonts.google.com>>

pikchr

Convert Pikchr Code to SVG

Description

This function converts a diagram description written in the Pikchr language into an SVG (Scalable Vector Graphics) format. Pikchr is a diagram language inspired by PIC, and this function allows you to easily embed Pikchr diagrams as SVG images in your HTML or Markdown documents.

Usage

```
pikchr(  
  code,  
  width = NULL,  
  height = NULL,  
  fontSize = "100%",  
  fontFamily = "Jost",  
  class = "pikchr",  
  align = "none",  
  css = NULL,  
  margin = NULL,  
  svgOnly = FALSE  
)
```

Arguments

code	A character string containing the diagram code written in the Pikchr language.
width	A character string representing the width of the rendered SVG. It accepts standard HTML values such as percentages ("75%"), pixels ("300px"), or "auto". If NULL (default), the intrinsic width from the SVG viewBox is used.
height	A character string representing the height of the rendered SVG. It accepts standard HTML values such as pixels ("300px") or "auto". If NULL (default), the intrinsic height from the SVG viewBox is used.
fontSize	A character string specifying the font size of the text within the SVG. It accepts standard HTML values such as percentages ("80%"), pixels, or keywords ("large"). Defaults to "100%".
fontFamily	A character string specifying the font family for the text in the diagram. Common values include "inherit" (to use the page's default font), "Arial", "Times New Roman", etc. Defaults to "Jost".
class	A character string specifying a CSS class to apply to the SVG. This can be used to style the SVG with external CSS rules. Defaults to "pikchr".
align	A character string specifying the alignment of the SVG within its container. Options are "center", "left", or "right". Defaults to "none", in which case no alignment wrapper is applied.

<code>css</code>	A character string containing extra CSS styles to apply directly to the SVG element. This allows additional customization beyond width, height, and font settings. If NULL, no extra styles are applied.
<code>margin</code>	A character string specifying the margin around the SVG element, formatted like a CSS margin rule (e.g., "10px 0 10px 0"). Defaults to "10px 0 10px 0".
<code>svgOnly</code>	Logical, whether to return only the raw SVG code (TRUE) or open the diagram in the Viewer window (FALSE, default).

Value

A character string containing the SVG diagram code if `svgOnly = TRUE`. Otherwise, the function opens the diagram in the Viewer window.

Examples

```
if(interactive()) {  
  pikchr('  
    arrow right 200% "Rmarkdown" "Source"  
    box rad 10px "Rmarkdown" "(knitr)" fit  
    arrow right 200% "HTML+SVG" "Output"  
    arrow <-> down from last box.s  
    box same "Pikchr" "(pikchr.c)" fit  
  ')  
}
```

Index

* **datasets**

google_fonts, [2](#)

google_fonts, [2](#)

pikchr, [3](#)