

Package ‘qualtRics’

June 25, 2026

Type Package

Title Download 'Qualtrics' Survey Data

Version 3.3.0

Description Provides functions to access survey results directly into R using the 'Qualtrics' API. 'Qualtrics' <<https://www.qualtrics.com/about/>> is an online survey and data collection software platform. See <<https://api.qualtrics.com/>> for more information about the 'Qualtrics' API. This package is community-maintained and is not officially supported by 'Qualtrics'.

License MIT + file LICENSE

URL <https://docs.ropensci.org/qualtRics/>,
<https://github.com/ropensci/qualtRics>

BugReports <https://github.com/ropensci/qualtRics/issues>

Imports archive, cli, dplyr (>= 1.0), fs, glue, httr, jsonlite, lifecycle, lubridate, purrr, readr, rlang, sjlabelled, stringr, tibble, tidyr, withr

Suggests covr, knitr, rmarkdown, testthat (>= 3.0.0), vcr (>= 1.2.0), webmockr

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Author Jasper Ginn [aut],
Jackson Curtis [ctb],
Shaun Jackson [ctb],
Samuel Kaminsky [ctb],
Eric Knudsen [ctb],
Joseph O'Brien [aut],
Daniel Seneca [ctb],
Julia Silge [aut] (ORCID: <<https://orcid.org/0000-0002-3671-836X>>),

Phoebe Wong [ctb],
Adam Pilipshen [aut, cre]
Maintainer Adam Pilipshen <martialmetrics@gmail.com>
Repository CRAN
Date/Publication 2026-06-25 13:40:02 UTC

Contents

all_mailinglists	2
all_surveys	3
column_map	4
extract_colmap	5
fetch_description	6
fetch_distributions	7
fetch_distribution_history	8
fetch_id	9
fetch_mailinglist	10
fetch_survey	11
list_distribution_links	15
metadata	16
qualtrics_api_credentials	17
read_survey	18
survey_questions	20
Index	22

all_mailinglists	<i>Retrieve a data frame of all mailing lists from Qualtrics</i>
------------------	--

Description

Retrieve a data frame of all mailing lists from Qualtrics

Usage

all_mailinglists()

Details

This function uses the Qualtrics XM Directory API. The directory it queries is discovered automatically from your account. If your account has more than one XM Directory, set the QUALTRICS_DIRECTORY_ID environment variable to the directory ID you want to use; otherwise the first directory returned by the API is used (with a warning).

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

# Retrieve a list of all mailing lists
mailinglists <- all_mailinglists()

## End(Not run)
```

all_surveys*Retrieve a data frame of all active surveys on Qualtrics*

Description

Retrieve a data frame of all active surveys on Qualtrics

Usage

```
all_surveys()
```

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

See Also

See <https://api.qualtrics.com/> for documentation on the Qualtrics API.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

# Retrieve a list of all surveys
surveys <- all_surveys()

# Retrieve a single survey
mysurvey <- fetch_survey(surveyID = surveys$id[6])
```

```
mysurvey <- fetch_survey(
  surveyID = surveys$id[6],
  save_dir = tempdir(),
  start_date = "2018-01-01",
  end_date = "2018-01-31",
  limit = 100,
  label = TRUE,
  unanswer_recode = "UNANS",
  verbose = TRUE
)

## End(Not run)
```

column_map

Retrieve a data frame containing survey column mapping

Description

Retrieve a data frame containing survey column mapping

Usage

```
column_map(surveyID)
```

Arguments

surveyID A string. Unique ID for the survey you want to download. Returned as id by the [all_surveys](#) function.

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

See Also

See <https://api.qualtrics.com/> for documentation on the Qualtrics API.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)
```

```
# Retrieve a list of surveys
surveys <- all_surveys()

# Retrieve column mapping for a survey
mapping <- column_map(surveyID = surveys$id[6])

# Retrieve a single survey, filtering for specific questions
mysurvey <- fetch_survey(
  surveyID = surveys$id[6],
  save_dir = tempdir(),
  include_questions = c("QID1", "QID2", "QID3"),
  verbose = TRUE
)

## End(Not run)
```

extract_colmap

Extract column map from survey data download

Description

Helper function to extract the column map attached to a response data download obtained from [fetch_survey\(\)](#) (using the default `add_column_map = TRUE`)

Usage

```
extract_colmap(respdata)
```

Arguments

respdata Response data including a column map dataframe as an attribute

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Examples

```
## Not run:
# Retrieve a list of surveys
surveys <- all_surveys()

# Retrieve a single survey
mysurvey <- fetch_survey(surveyID = surveys$id[6])

# Extract column mapping for survey
```

```
extract_colmap(mysurvey)

## End(Not run)
```

fetch_description	<i>Download complete survey description using the Qualtrics v3 "Get Survey" API endpoint.</i>
-------------------	---

Description

Download complete survey description using the Qualtrics v3 "Get Survey" API endpoint.

Usage

```
fetch_description(surveyID, elements = NULL, legacy = FALSE, ...)
```

Arguments

surveyID	A string. Unique ID for the survey you want to download. Returned as "id" by the all_surveys function.
elements	A character vector. Lists elements of survey definition to be maintained. Possible elements are "metadata", "surveyoptions", "flow", "blocks", "questions", "responsesets", and/or "scoring" (case-insensitive). If legacy = TRUE, then possible elements are "metadata", "questions", "responsecounts", "blocks", "flow", "embedded_data", and/or "comments".
legacy	Logical. If TRUE, will use older Get Survey API endpoint via a call to legacy function metadata .
...	Additional options, only used when legacy = TRUE. User may pass an argument called questions, a vector containing the names of questions for which you want to return metadata.

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Value

A list containing survey description metadata. The contents of the returned list depend on elements.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

# Retrieve a list of surveys
surveys <- all_surveys()

# Get description for a survey
descrip <- fetch_description(surveyID = surveys$id[6])

# Get metadata with specific elements
descrip_specific <- fetch_description(
  surveyID = id,
  elements = c("questions", "flow")
)

## End(Not run)
```

fetch_distributions	<i>Download distribution data for a survey from Qualtrics</i>
---------------------	---

Description

Download distribution data for a survey from Qualtrics

Usage

```
fetch_distributions(surveyID)
```

Arguments

surveyID String. Unique survey ID for the distribution data you want to download.

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

surveys <- all_surveys()
distributions <- fetch_distributions(surveys$id[1])

## End(Not run)
```

fetch_distribution_history

Download distribution history data for a distribution from Qualtrics

Description

Download distribution history data for a distribution from Qualtrics

Usage

```
fetch_distribution_history(distributionID)
```

Arguments

`distributionID` String. Unique distribution ID for the distribution history you want to download.

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

surveys <- all_surveys()
distributions <- fetch_distributions(surveys$id[1])
distribution_history <- fetch_distribution_history(distributions$id[1])
```



```
## End(Not run)
```

fetch_id	<i>Fetch a unique Qualtrics survey ID based on survey name in the Qualtrics UI</i>
----------	--

Description

Fetch a unique Qualtrics survey ID based on survey name in the Qualtrics UI

Usage

```
fetch_id(.data, survey_name, partial_match = FALSE)
```

Arguments

.data	Data frame of active surveys created by the function all_surveys() .
survey_name	String. Name of the survey as it appears in the Qualtrics UI. Must be unique to be passed to <code>fetch_id()</code> .
partial_match	Boolean. Will match all surveys containing the exact string provided. Defaults to FALSE, which matches against the entire name.

Details

Survey names in the Qualtrics platform are not required to be unique, but the `survey_name` argument for this function *must* be unique. If input results in multiple surveys being matched, will error with a list of up to 5 matches & their IDs

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

# Retrieve a list of surveys
surveys <- all_surveys()

# Retrieve surveyID for a unique survey
my_id <- fetch_id(surveys, "Unique Survey Name")

## End(Not run)
```

fetch_mailinglist	<i>Download a mailing list from Qualtrics</i>
-------------------	---

Description

Download a mailing list from Qualtrics

Usage

```
fetch_mailinglist(mailinglistID)
```

Arguments

mailinglistID String. Unique ID for the mailing list you want to download. Returned as `mailingListId` by the [all_mailinglists](#) function.

Details

This function uses the Qualtrics XM Directory API. The directory it queries is discovered automatically from your account. If your account has more than one XM Directory, set the `QUALTRICS_DIRECTORY_ID` environment variable to the directory ID you want to use; otherwise the first directory returned by the API is used (with a warning).

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

# Retrieve a list of all mailing lists
mailinglists <- all_mailinglists()

# Retrieve a single mailing list
mailinglist <- fetch_mailinglist(mailinglists$mailingListId[1])

## End(Not run)
```

fetch_survey	<i>Download a survey and import it into R</i>
--------------	---

Description

Download a Qualtrics survey you own via API and import the survey directly into R.

Usage

```
fetch_survey(
  surveyID,
  limit = NULL,
  start_date = NULL,
  end_date = NULL,
  time_zone = NULL,
  include_display_order = TRUE,
  include_metadata = NULL,
  include_questions = NULL,
  include_embedded = NULL,
  unanswer_recode = NULL,
  unanswer_recode_multi = unanswer_recode,
  breakout_sets = TRUE,
  import_id = FALSE,
  label = TRUE,
  convert = TRUE,
  add_column_map = TRUE,
  add_var_labels = TRUE,
  strip_html = TRUE,
  col_types = NULL,
  verbose = TRUE,
  tmp_dir = tempdir(),
  last_response = deprecated(),
  force_request = deprecated(),
  save_dir = deprecated()
)
```

Arguments

surveyID	String. Unique ID for the survey you want to download. Returned as id by the all_surveys function.
limit	Integer. Maximum number of responses exported. Defaults to NULL (download all responses).
start_date, end_date	POSIXct, POSIXlt, or Date object, or length-1 string equivalent of form "YYYY-MM-DD" or "YYYY-MM-DD HH:MM:SS". ("/" is also acceptable in place of "-".) Only export survey responses that were recorded within the range specified by one or both arguments (i.e. referencing <i>RecordedDate</i>). Each defaults to

	NULL (unbounded). See Details for important information about both the package and Qualtrics' handling of start/end times.
time_zone	String. Time zone to use for date/time metadata variables in response dataframe (e.g. <i>StartDate</i>). Must match a time zone name from <code>base::OlsonNames()</code> . Defaults to NULL, which uses the current system timezone (from <code>base::Sys.timezone()</code>). Also applied to arguments <i>start_date</i> and/or <i>expiration_date</i> when given Date or string objects (see above); ignored when these arguments are given POSIXlt/POSIXct objects.
include_display_order	Logical. If TRUE, download from surveys using block/question/answer display randomization will include contain additional variables indicating the randomization pattern used for each case. Defaults to FALSE.
include_metadata, include_questions, include_embedded	Character vector. Specify variables to include in download. Defaults to NULL (keep all). NA or <code>character()</code> excludes all variables for that category. See Details for more on using each inclusion argument.
unanswer_recode	Integer-like. Recode seen-but-unanswered (usually skipped) questions using this value. Defaults to NA
unanswer_recode_multi	Integer-like. Recode seen-but-unanswered multi-select questions (checkboxes) using this value. Defaults to value for <i>unanswer_recode</i> .
breakout_sets	Logical. If TRUE multi-value fields (e.g. each option of a multi-select multiple choice questions) will be returned as separate columns. If FALSE, will be returned as 1 column with each element containing all values.
import_id	Logical. If TRUE, column names will use Qualtrics import IDs (e.g. "QID123") instead of user-modifiable names (e.g. default names like "Q3" or custom names). Defaults to FALSE (user-modifiable names). Note that this also affects (otherwise unmodifiable) names of metadata columns—see the "include_metadata" section in Details below.
label	Logical. If TRUE (default), will return text of answer choices, instead of recoded values (FALSE).
convert	Logical. If TRUE, then the <code>fetch_survey()</code> function will convert certain question types (e.g. multiple choice) to proper data type in R. Defaults to TRUE.
add_column_map	Logical. Add an attribute to the returned response data frame containing metadata associated with the response download, including variable names, question/choice text, and Qualtrics import IDs. This column map can be subsequently obtained using <code>extract_colmap()</code> Defaults to TRUE.
add_var_labels	Logical. If TRUE, then the item description from each variable (equivalent to the one in the column map) will be added as a "label" attribute using <code>sjlabelled::set_label()</code> . Useful for reference as well as cross-compatibility with other stats packages (e.g., Stata, see documentation in <code>sjlabelled</code>). Defaults to TRUE.
strip_html	Logical. If TRUE, then remove HTML tags from variable descriptions. Defaults to TRUE. Ignored if <i>add_column_map</i> and <i>add_var_labels</i> are both FALSE.

col_types	Optional. This argument provides a way to manually overwrite column types that may be incorrectly guessed. Takes a <code>readr::cols()</code> specification. See example below and <code>readr::cols()</code> for formatting details. Defaults to NULL. Overwritten by <code>convert = TRUE</code> .
verbose	Logical. If TRUE, verbose messages will be printed to the R console. Defaults to TRUE.
tmp_dir	Path to filesystem directory. Qualtrics returns response data in compressed (zip) form. To extract raw data, the zip file must be briefly written to disk (the file is then promptly deleted). By default, the system's temporary directory is used for this (see <code>tempdir()</code>), but users needing more control can specify an alternate location here.
last_response	Deprecated.
force_request	Deprecated.
save_dir	Deprecated.

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

start_date & end_date arguments

The Qualtrics API endpoint for this function treats `start_date` and `end_date` slightly differently; `end_date` is *exclusive*, meaning only responses recorded up to the moment *before* the specified `end_date` will be returned. This permits easier automation; a previously-used `end_date` can become the `start_date` of a subsequent request without downloading duplicate records.

As a convenience for users working interactively, the `qualtrics` package also accepts Date(-like) input to each argument, which when used implies a time of 00:00:00 on the given date (and time zone). When a Date(-like) is passed to `end_date`, however, the date will be incremented by one before making the API request. This adjustment is intended to provide interactive users with more intuitive results; for example, specifying "2022/06/02" for both `start_date` and `end_date` will return all responses for that day, (instead of the zero responses that would return if `end_date` was not adjusted).

Inclusion/exclusion arguments

The three `include_*` arguments each have different requirements:

`include_metadata`:

Elements must be one of the 17 Qualtrics metadata variables, listed here in their default order: *StartDate* (`startDate`), *EndDate* (`endDate`), *Status* (`status`), *IPAddress* (`ipAddress`), *Progress* (`progress`), *Duration (in seconds)* (`duration`), *Finished* (`finished`), *RecordedDate* (`recordedDate`), *ResponseId* (`_recordId`), *RecipientLastName* (`recipientLastName`), *RecipientFirstName* (`recipientFirstName`), *RecipientEmail* (`recipientEmail`), *ExternalReference* (`externalDataReference`), *LocationLatitude* (`locationLatitude`), *LocationLongitude* (`locationLongitude`), *DistributionChannel* (`distributionChannel`), *UserLanguage* (`userLanguage`).

Names in parentheses are those returned by the API endpoint when `import_id` is set to `TRUE`. The argument `include_metadata` can accept either format regardless of `import_id` setting, and names are not case-sensitive. Duplicate elements passed to `include_metadata` will be silently dropped, with the de-duplicated variable located in the first position.

`include_questions:`

Qualtrics uniquely identifies each question with an internal ID that takes the form "QID" followed by a number, e.g. *QID5*. When using `include_questions`, these internal IDs must be used rather than user-customizable variable names (which need not be unique in Qualtrics). If needed, a column map linking customizable names to QID's can be quickly obtained by calling:

```
my_survey <- fetch_survey(
  surveyID = {survey ID},
  limit = 1,
  add_column_map = TRUE
)
extract_colmap(my_survey)
```

Note that while there is one QID for each "question" in the Qualtrics sense, each QID may still map to multiple columns in the returned data frame. If, for example, a "question" with ID *QID5* is a multiple-choice item with a text box added to the third choice, the returned data frame may have two related columns: "*QID5*" for the multiple choice selection, and "*QID5_3_TEXT*" for the text box (or, more typically, their custom names). Setting `include_questions = "QID5"` will always return both columns. Similarly, "matrix" style multiple-choice questions will have a column for each separate row of the matrix. Also, when `include_display_order = TRUE`, display ordering variables for any randomization will be included. Currently, separating these sub-questions via the API does not appear possible (e.g., `include_questions = "QID5_3_TEXT"` will result in an API error).

`include_embedded:`

This argument accepts the user-specified names of any embedded data variables in the survey being accessed.

See Also

See <https://api.qualtrics.com/> for documentation on the Qualtrics API.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

# Retrieve a list of surveys
surveys <- all_surveys()

# Retrieve a single survey
my_survey <- fetch_survey(surveyID = surveys$id[6])
```

```
my_survey <- fetch_survey(  
  surveyID = surveys$id[6],  
  start_date = "2018-01-01",  
  end_date = "2018-01-31",  
  limit = 100,  
  label = TRUE,  
  unanswer_recode = 999,  
  verbose = TRUE,  
  # Manually override EndDate to be a character vector  
  col_types = readr::cols(EndDate = readr::col_character())  
)  
  
## End(Not run)
```

list_distribution_links

Download distribution links for a distribution from Qualtrics

Description

Download distribution links for a distribution from Qualtrics

Usage

```
list_distribution_links(distributionID, surveyID)
```

Arguments

distributionID String. Unique distribution ID for the distribution links you want to download.
surveyID String. Unique ID for the survey you want to download.

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Examples

```
## Not run:  
# Register your Qualtrics credentials if you haven't already  
qualtrics_api_credentials(  
  api_key = "<YOUR-API-KEY>",  
  base_url = "<YOUR-BASE-URL>"  
)
```

```

surveys <- all_surveys()
distributions <- fetch_distributions(surveys$id[1])
distribution_links <- list_distribution_links(distributions$id[1], surveyID = surveys$id[1])

## End(Not run)

```

metadata

Download metadata for a survey

Description

Using this function, you can retrieve metadata about your survey. This information includes question metadata (type, options, choices, etc), number of responses, general metadata, survey flow, etc.

Usage

```
metadata(surveyID, get = NULL, questions = NULL)
```

Arguments

surveyID	A string. Unique ID for the survey you want to download. Returned as "id" by the all_surveys function.
get	A character vector containing any of the following: "metadata", "questions", "responsecounts", "blocks", "flow", "embedded_data", or "comments". Will return included elements. By default, the function returns the "metadata", "questions", and "responsecounts" elements. See examples below for more information.
questions	Character vector containing the names of questions for which you want to return metadata. Defaults to NULL (all questions).

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

Examples

```

## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)

# Retrieve a list of surveys
surveys <- all_surveys()

```



```

# Get metadata for a survey
md <- metadata(surveyID = surveys$id[6])

# Get metadata with specific elements
md_specific <- metadata(
  surveyID = id,
  get = c("flow")
)

# Get specific question metadata
question_specific <- metadata(
  surveyID = id,
  get = c("questions"),
  questions = c("Q1", "Q2")
)

# Example of a metadata file
file <- system.file("extdata", "metadata.rds", package = "qualtRics")

# Load
metadata_ex <- readRDS(file = file)

## End(Not run)

```

qualtrics_api_credentials

Install Qualtrics credentials in your .Renvirom file for repeated use

Description

This function adds your Qualtrics API key and base URL to your .Renvirom file so it can be called securely without being stored in your code. After you have installed these two credentials, they can be called any time with `Sys.getenv("QUALTRICS_API_KEY")` or `Sys.getenv("QUALTRICS_BASE_URL")`. If you do not have an .Renvirom file, the function will create one for you. If you already have an .Renvirom file, the function will append the key to your existing file, while making a backup of your original file for disaster recovery purposes.

Usage

```

qualtrics_api_credentials(
  api_key,
  base_url,
  overwrite = FALSE,
  install = FALSE,
  report = FALSE
)

```

Arguments

api_key	The API key provided to you from Qualtrics formatted in quotes. Learn more about Qualtrics API keys at https://api.qualtrics.com/
base_url	The institution-specific base URL for your Qualtrics account, formatted in quotes, without the protocol (do not include https://). Find your base URL at https://api.qualtrics.com/
overwrite	If TRUE, will overwrite existing Qualtrics credentials that you already have in your .Renviron file.
install	If TRUE, will install the key in your .Renviron file for use in future sessions. Defaults to FALSE (single session use).
report	If TRUE, ignores other arguments and outputs credentials as a 2-element named vector.

Examples

```
## Not run:
qualtrics_api_credentials(
  api_key = "<YOUR-QUALTRICS_API_KEY>",
  base_url = "<YOUR-QUALTRICS_BASE_URL>",
  install = TRUE
)
# Reload your environment so you can use the credentials without restarting R
readRenviron("~/Renviron")
# You can check it with:
Sys.getenv("QUALTRICS_API_KEY")

# If you need to overwrite existing credentials:
qualtrics_api_credentials(
  api_key = "<YOUR-QUALTRICS_API_KEY>",
  base_url = "<YOUR-QUALTRICS_BASE_URL>",
  overwrite = TRUE,
  install = TRUE
)
# Reload your environment to use the credentials

## End(Not run)
```

read_survey

Read a CSV file exported from Qualtrics

Description

Reads comma separated CSV files generated by Qualtrics software. The second line containing the variable labels is imported. Repetitive introductions to matrix questions are automatically removed. Variable labels are stored as attributes.

Usage

```
read_survey(
  file_name,
  strip_html = TRUE,
  import_id = FALSE,
  time_zone = NULL,
  legacy = FALSE,
  add_column_map = TRUE,
  add_var_labels = TRUE,
  col_types = NULL
)
```

Arguments

file_name	String. A CSV data file.
strip_html	Logical. If TRUE, then remove HTML tags from variable descriptions. Defaults to TRUE.
import_id	Logical. If TRUE, use Qualtrics import IDs instead of question IDs as column names. Defaults to FALSE.
time_zone	String. A local timezone to determine response date values. Defaults to NULL which corresponds to UTC time. See "Dates and Times" from Qualtrics for more information on format.
legacy	Logical. If TRUE, then import "legacy" format CSV files (as of 2017). Defaults to FALSE.
add_column_map	Logical. If TRUE, then a column map data frame will be added as an attribute to the main response data frame. This column map captures Qualtrics-provided metadata associated with the response download, such as an item description and internal ID's. Defaults to TRUE.
add_var_labels	Logical. If TRUE, then the item description from each variable (equivalent to the one in the column map) will be added as a "label" attribute using <code>sjlabelled::set_label()</code> . Useful for reference as well as cross-compatibility with other stats packages (e.g., Stata, see documentation in <code>sjlabelled</code>). Defaults to TRUE.
col_types	Optional. This argument provides a way to manually overwrite column types that may be incorrectly guessed. Takes a <code>readr::cols()</code> specification. See example below and <code>readr::cols()</code> for formatting details. Defaults to NULL.

Value

A data frame. Variable labels are stored as attributes. They are not printed on the console but are visible in the RStudio viewer.

Examples

```
## Not run:
# Generic use of read_survey()
df <- read_survey("<YOUR-PATH-TO-CSV-FILE>")
```

```
## End(Not run)
# Example using current data format
file <- system.file("extdata", "sample.csv", package = "qualtRics")
df <- read_survey(file)

# Example using legacy data format
file <- system.file("extdata", "sample_legacy.csv", package = "qualtRics")
df <- read_survey(file, legacy = TRUE)

# Example changing column type
file <- system.file("extdata", "sample.csv", package = "qualtRics")
# Force EndDate to be a string
df <- read_survey(file, col_types = readr::cols(EndDate = readr::col_character()))
```

survey_questions	<i>Retrieve a data frame containing question IDs and labels</i>
------------------	---

Description

Retrieve a data frame containing question IDs and labels

Usage

```
survey_questions(surveyID)
```

Arguments

surveyID	A string. Unique ID for the survey you want to download. Returned as <code>id</code> by the all_surveys function.
----------	---

Details

If the request to the Qualtrics API made by this function fails, the request will be retried. If you see these failures on a 500 error (such as a 504 error) be patient while the request is retried; it will typically succeed on retrying. If you see other types of errors, retrying is unlikely to help.

See Also

See <https://api.qualtrics.com/> for documentation on the Qualtrics API.

Examples

```
## Not run:
# Register your Qualtrics credentials if you haven't already
qualtrics_api_credentials(
  api_key = "<YOUR-API-KEY>",
  base_url = "<YOUR-BASE-URL>"
)
```

```
# Retrieve a list of surveys
surveys <- all_surveys()

# Retrieve questions for a survey
questions <- survey_questions(surveyID = surveys$id[6])

# Retrieve a single survey, filtering for specific questions
mysurvey <- fetch_survey(
  surveyID = surveys$id[6],
  save_dir = tempdir(),
  include_questions = c("QID1", "QID2", "QID3"),
  verbose = TRUE
)

## End(Not run)
```

Index

`all_mailinglists`, [2](#), [10](#)
`all_surveys`, [3](#), [4](#), [6](#), [11](#), [16](#), [20](#)
`all_surveys()`, [9](#)

`base::OlsonNames()`, [12](#)
`base::Sys.timezone()`, [12](#)

`column_map`, [4](#)

`extract_colmap`, [5](#)
`extract_colmap()`, [12](#)

`fetch_description`, [6](#)
`fetch_distribution_history`, [8](#)
`fetch_distributions`, [7](#)
`fetch_id`, [9](#)
`fetch_mailinglist`, [10](#)
`fetch_survey`, [11](#)
`fetch_survey()`, [5](#), [12](#)

`list_distribution_links`, [15](#)

`metadata`, [6](#), [16](#)

`qualtrics_api_credentials`, [17](#)

`read_survey`, [18](#)
`readr::cols()`, [13](#), [19](#)

`sjlabelled::set_label()`, [12](#), [19](#)
`survey_questions`, [20](#)

`tempdir()`, [13](#)